


GUARD HARDENER® RD

RISING DAMP



STOPS RISING DAMP AND DRIES WALLS

- ✓ **PREVENTS RISING DAMP IN THE BASE OF WALLS**
- ✓ **REMEDIES DAMP AND SALTPETRE PROBLEMS**
- ✓ **CONSOLIDATES AND CRYSTALLISES MATERIALS**
- ✓ **TREATMENT BY INJECTION**
- ✓ **INTERIOR AND EXTERIOR**

PRODUCT DESCRIPTION

Guard Hardener® RD is a product for treating humidity in walls, rising damp, efflorescence and surface salts. It dries and consolidates friable substrates damaged by intrusion of water and damp. It therefore mitigates problems of rising damp.

Guard Hardener® RD is applied by injection into walls. Very dense, Guard Hardener® RD uses water as a vehicle and makes use of it to harden and mineralise to create a waterproof barrier that will prevent any rising damp.

USE

Guard Hardener® RD can be used indoors and out of doors wherever once-for-all drying is required. It can be applied to facades and walls in cement, concrete, natural stone, brick...

CHEMICAL NATURE

- Mixture of sodium silicate in an aqueous phase.

ADVANTAGES AND CHARACTERISTICS

- Solves damp problems.
- Creates a barrier to stop problems rising damp.
- Consolidates materials.
- Colourless.
- Water-based product, solvent-free.
- Non corrosive, non irritant.

CONTAINERS


5 and 25 litres.

TECHNICAL DATA

Physical state at 20 °C	: Liquid
Appearance	: Uncoloured
Odour	: None
pH	: 12 ± 0.5
Boiling point [°C]	: 100 °C
Density	: 1.25 ± 0.01
Solubility in water [vol/vol]	: Total
Flash point [°C]	: Not applicable
VOCs	: > 1g/l*

HOW TO USE

- Treatment is by injection in the base of the wall to be treated, 10 cm higher than the ground.
- Drill 2 staggered rows of holes (\varnothing 15 - 30 mm) not more than 30 cm apart at an angle of 30° to 40° downwards to a depth of 2/3 of the thickness of the wall.
- For a very thick wall (> 60 cm) the treatment must be applied from both sides.
- Inject the product into each hole until it comes back out of the hole, then seal with cement containing 3% to 5% **Guard Hardener® RD**.
- Make sure that no hole communicates with a cavity, causing running water. In the case of a cavity, plug it with a mixture of cement and product and re-drill after 24 hours.
- Full effects achieved after drying for several weeks, depending on the composition of the wall.



APPLICATION TOOLS

- Apply by gravity or with an injections machine.

COVERAGE

The following values are for guidance only:

- **Treatment by injection against rising damp:**
± 2 to 3 litres / meter (for a wall of 20 cm thickness).

TIPS AND TRICKS

Guard Hardener® RD can be applied by spray in case of damp friable surfaces (indoor walls, basements...). In this case, apply the product neat in one or two layers (drying time between each layer: 1 hour)

CLEANING YOUR EQUIPMENT

- Clean tools and equipment immediately after use with water.

STORAGE

- Keep in a dry place (between 5°C and 30°C).
- Storage: 24 months following the production date when kept in the original unopened container.

RECOMMENDATIONS

- For ideal application and effective results, **Guard Hardener® RD** must be used when the substrate temperature is between 5°C and 30°C.
- Do not apply in rain or very hot weather. Air temperature between 5°C and 30°C.
- Do not apply to plaster or fragile materials, organic, metallic or impermeable materials.
- Product is alkaline. Handle preferably with gloves and goggles. Protect painted surfaces, glass, tiles and light alloys (aluminium, chrome, copper, zinc, etc). Accidental splashes should be rinsed off immediately with water.
- Do not dilute or mix with another product.

HEALTH AND SAFETY

- **Respiratory protection** : Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed.
- **Hand protection** : Wear rubber gloves resistant to chemical products.
- **Skin protection** : No special protective clothing or skin protection is required under normal conditions of use.
- **Eye protection** : If there is a real risk of splashing, wear protective goggles.
- **If swallowed** : Do not induce vomiting. Contact a doctor or a specialist.

KEEP OUT OF THE REACH OF CHILDREN

TECHNICAL SUPPORT

GUARD INDUSTRY

7 rue Gutenberg • 93108 MONTREUIL Cedex • FRANCE

Tél: +33 (0)1.55.86.17.60 • Fax: +33 (0)1.48.58.16.89

E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website
www.guardindustry.com

Last updated : 09/12/2013